

# TECHNICAL DOCUMENTATION

## PROFLO +

FLOCCULENT FOR PAINTS, VARNISHES, AND ADHESIVES FOR USE IN SPRAY BOOTHS, TUNNELS AND ROBOTS WITH A WATER CURTAIN ( additive to PROCOAGU ).



### DÉSIGNATION

**PROFLO+** is a polymeric dispersing solution for the treatment of water in spray booths, tunnels and robots for paint and varnishes.

**PROFLO+** can be used for the treatment of residual water containing adhesives or any other pollutant.

**PROFLO+** should be used to complement to **PROCOAGU** in order to obtain a perfect separation of paint overspray.



### CHARACTERISTICS

APPEARANCE†	:	thick colourless liquid
pH-value	:	neutral
REACTION	:	neutral, non-active on ferrous and non-ferrous metals.
SOLUBILITY	:	totally water soluble
ENVIRONMENTAL EFFECT	:	biodegradable

### PREPARATION AND DOSE (see calculation and dosage example)

- 1 - For the treatment of a new bath : 0.7 % of the volume of the bath.
- 2 - Each day, add into the installation 5 % of the collected paint overspray and 0.6% of the water quantity added into the system.
- 3 - Order of mixing : 5 to 8 minutes after PROCOAGU
- 4 - Doses should be carried out manually or automatically with a dosing-pump.  
Doses should be strictly adhered to.
- 5 - In the absence of an automatic skimming system, varnish and paint sediments should be skimmed manually every evening or better still twice a day.



Doses should be strictly adhered to.  
SHAKE WELL BEFORE USING